

# ELECTRIC PAD HEATERS



Electric heating pad that is applied directly to the source for reliable cold-weather starting.

## BENEFITS

- Even heat distribution
- May be installed in sub-zero temperatures
- Reduces engine wear by improving the flow of engine oil
- Reduces pump cavitation, blown seals and burst hydraulic components
- Easy Peel-and-Stick application; mounts to any smooth, metal surface

**12/24 VOLTS DC – 120/220 VOLTS AC**



## FEATURES

- Models available in 120 and 240 VAC
- Models available in 12 and 24 VDC
- Aluminum backing

# ELECTRIC PAD HEATERS

PART NUMBER	DESCRIPTION			APPLICATION				
	WATTS VOLTS	AMP. DRAW	INCHES MM	ENGINE OIL	DIESEL FUEL	WATER	HYDRAULIC OIL	POWER PLUG
EH-2801	125 120 AC	1	2.25 X 4 57 X 102	1.5-4 qt. 1.3-3.8 L	N/A	5-20 gal. 18.9-75.7 L	1-10 gal. 3.8-37.9 L	3-Prong NEMA 5-15P
EH-2802	250 120 AC	2.1	3.5 X 4.5 89 X 114	4.5-12 qt. 4.3-11.4 L	N/A	24-45 gal. 90.9-170.3 L	10-30 gal. 37.9-113.6 L	3-Prong NEMA 5-15P
EH-2805	500 120 AC	4.2	5 X 7 127 X 178	3-6 gal. 11.4-22.7 L	40-60 gal. 151.4-227.1 L	50-100 gal. 189.2-378.5 L	20-50 gal. 75.7-189.3 L	3-Prong NEMA 5-15P
EH-2810	1000 120 AC	8.3	6 X 10.75 152 X 273	6.5-12 gal. 24.6-45.4 L	50-100 gal. 189.3-378.5 L	100-200 gal. 378.5-757 L	50-100 gal. 189.3-378.5 L	3-Prong NEMA 5-15P
EH-3201	125 220 AC	0.1	2.25 X 4 57 X 102	1.5-4 qt. 1.3-3.8 L	N/A	5-20 gal. 18.9-75.7 L	1-10 gal. 3.8-37.9 L	NONE
EH-3202	250 220 AC	1.1	3.5 X 4.5 89 X 114	4.5-12 qt. 4.3-11.4 L	N/A	24-45 gal. 90.9-170.3 L	10-30 gal. 37.9-113.6 L	NONE
EH-3205	500 220 AC	2.3	5 X 7 127 X 178	3-6 gal. 11.4-22.7 L	40-60 gal. 151.4-227.1 L	50-100 gal. 189.2-378.5 L	20-50 gal. 75.7-189.3 L	NONE
EH-3210	1000 220 AC	4.5	6 X 10.75 152 X 273	6.5-12 gal. 24.6-45.4 L	50-100 gal. 189.3-378.5 L	100-200 gal. 378.5-757 L	50-100 gal. 189.3-378.5 L	NONE
EH-2874	80 12 DC	6.7	1.5 X 8 38 X 203	N/A	N/A	3-12 gal. 11.4-45.4 L	.5-6 qt. .5-5.7 L	NONE
EH-3659	250 12 DC	20.8	5 X 5 127 X 127	N/A	N/A	24-45 gal. 90.9-170.3 L	10-30 gal. 37.9-113.6 L	NONE
EH-3660	350 12 DC	30.8	7 X 5 178 X 127	N/A	N/A	35-65 gal. 132.5-246.1 L	15-45 gal. 56.8-170.3 L	NONE
EH-4111	80 24 DC	3.4	4 X 1.5 101 X 38	N/A	N/A	3-12 gal. 11.4-45.4 L	.5-6 qt. .5-5.7 L	NONE
EH-4608	80 12 DC	6.7	3.25 X 1.75 83 X 45	N/A	N/A	3-12 gal. 132.5-246.1 L	.5-6 qt. .5-5.7 L	NONE
EH-6282	7 12 DC	0.6	1 X 2 25 X 51	Typical Application: spot heating for small valves or fittings				NONE