SAFETY DATA SHEET

OSHA HCS (29 CFR 1910.1200)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Chemical Name Mixture CAS No. Mixture

Trade Name PHILLIPS & TEMRO 8200327,8201277

Product Code SP-500707, SP-500708

Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Starting Fluid
Uses Advised Against None

Company Identification Spray Products Corporation

P.O. Box 737

Norristown, PA 19404

Telephone (610) 277-1010 Fax (610) 277-4390

E-Mail (competent person) <u>johnd@sprayproducts.com</u>

Emergency telephone number

Emergency Phone No. Transportation Emergency: CHEMTREC 24 hr. 1-800-424-

9300 / 1 (703) 527-3887 (Collect calls accepted)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the substance or mixture

OSHA HCS (29 CFR 1910.1200)

Label elements

Hazard Symbol

Flam. Gas 1; Liquefied gas; Skin Irrit. 2; Carc. 2; Repr. 2; STOT SE 3



Signal word(s)

Hazard Statement(s)

Extremely flammable gas.

Contains gas under pressure; may explode if heated.

Causes skin irritation.

Suspected of causing cancer.

Suspected of damaging the unborn child. May cause drowsiness or dizziness.

Precautionary Statement(s) Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood. Keep away from heat/sparks/open flames/hot surfaces. – No smoking. Wear protective gloves/protective clothing/eye protection/face protection.

Avoid breathing dust/fume/gas/mist/vapours/spray.

Wash hands and exposed skin after use.
Use only outdoors or in a well-ventilated area.

Protect from sunlight and do not expose to temperatures exceeding 50

°C/122 °F.

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Eliminate all ignition sources if safe to do so.

Other hazards

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Ingredient(s)	% wt. *	CAS No.	Hazard classification
			Flam. Liq. 1; H224
Diethyl Ether	55 - 65	60-29-7	Acute Tox. 4; H302
			STOT SE 3; H336
			Flam. Liq. 2; H225
			Skin Irrit. 2; H315
Naptha (petroleum) hydrotreated light	20 - 30	64742-49-0	Asp. Tox. 1; H304
· · · · · · · · · · · · · · · · · · ·			STOT SE 3; H336
			Aquatic Acute 2; H401
			Aquatic Chronic 2; H11
Carbon Dioxide	10 - 15	124-38-9	Compressed dissolved gas; H280
Ethanol	<5	64-17-5	Flam. Liq. 2; H225
Litiation	ζ3	04-17-5	Eye Irrit. 2; H319
Chloroethane	< 2	75-00-3	Flam. Gas 1; H220
Chloroethane	\ Z	75-00-5	Carc. 2; H351
Petroleum Distillate	< 1	Mixture	Asp. Tox. 1; H304
			Flam. Liq. 2; H225
			Repr. 2; H361
			Skin Irrit. 2; H315
			Eye Irrit. 2; H319
Toluene	< 0.5	108-88-3	Asp. Tox. 1; H304
			STOT SE 3; H336
			STOT RE 2; H373
			Aquatic Acute 2; H401
			Aquatic Chronic 3; H412

Additional Information - None

SECTION 4: FIRST AID MEASURES



Description of first aid measures

Inhalation Move person to fresh air. If breathing is labored, administer oxygen. If

symptoms develop, obtain medical attention.

Skin Contact Wash affected skin with soap and water. If irritation (redness, rash,

blistering) develops, get medical attention. Take off contaminated

clothing and wash it before reuse.

Eye Contact Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. If eye irritation

persists: Get medical advice/attention.

Ingestion Do not induce vomiting. Do not give anything by mouth to an

unconscious person. Get immediate medical attention.

Most important symptoms and effects, both acute and

May cause drowsiness or dizziness.

delayed

Indication of any immediate medical attention and special treatment needed

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Page: 2/7

^{*} The exact percentage withheld as a trade secret in accordance with 29 CFR 1910.1200.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

-Suitable Extinguishing Media Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

Keep containers cool by spraying with water if exposed to fire.

-Unsuitable Extinguishing Media Do not use water jet.

Special hazards arising from the substance or

mixture

Contains gas under pressure; may explode if heated.

Advice for fire-fighters A self contained breathing apparatus and suitable protective clothing

should be worn in fire conditions. Keep containers cool by spraying

with water if exposed to fire.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and

emergency procedures

Eliminate sources of ignition. Avoid contact with skin and eyes. Wear protective gloves/protective clothing/eye protection/face protection.

Avoid breathing gas / vapours.

Environmental precautions Prevent liquid entering sewers, basements and work pits. Avoid

release to the environment.

Methods and material for containment and cleaning up Cover spills with inert absorbent material. Collect spillage.Transfer to a

container for disposal or recovery.

Reference to other sections None
Additional Information None

SECTION 7: HANDLING AND STORAGE

Precautions for safe handling

Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking. Avoid contact with skin and eyes. Avoid breathing gas / vapours. Use product in a well-ventilated area only.

Conditions for safe storage, including any incompatibilities

-Storage temperature Store in a well-ventilated place. Protect from sunlight. Do not expose to

temperatures exceeding 50°C/ 122°F. Keep container tightly closed.

Store locked up.

-Incompatible materials This product should be stored away from sources of strong heat or

oxidizing chemicals.

Specific end use(s) Starting Fluid

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Occupational Exposure Limits

		(8hr TWA)		(ST		
SUBSTANCE.	CAS No.	PEL (OSHA)	TLV (ACGIH)	PEL (OSHA)	TLV (ACGIH)	Note:
Alkanes (C5-C6)		500 ppm**	1500 mg/m ³			**n-heptane
Diethyl ether	60-29-7	400 ppm	400 ppm		500 ppm	
Chloroethane	75-00-3	1000 ppm	100 ppm*			*A3
Carbon dioxide	124-38-9	5000 ppm	5000 ppm		30,000 ppm	
Toluene	108-88-3	200 ppm	20 ppm	300 ppm*		*10-min. Ceiling

#Assure minimum oxygen content of work atmosphere. *A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans

Recommended monitoring method NIOSH 1500 (hydrocarbons, B.P. 36 - 126 °C); NIOSH 1610 (Ethyl

ether); NIOSH 2519 (Ethyl chloride); NIOSH 1501 (Aromatic

hydrocarbons)

Exposure controls

Appropriate engineering controls Provide adequate ventilation to ensure that the occupational exposure

limit is not exceeded.

Personal protection equipment

Eye/face protection Wear protective eyewear (goggles, face shield, or safety glasses).



Skin protection (Hand protection/ Other) Wear suitable gloves if prolonged skin contact is likely. Check with

protective equipment manufacturer's data.

Respiratory protection Normally no personal respiratory protection is necessary. In case of insufficient ventilation, wear suitable respiratory equipment. Check with

protective equipment manufacturer's data.

7

Thermal hazards Not normally required. Use gloves with insulation for thermal

protection, when needed.

Environmental Exposure ControlsAvoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance Gas under pressure

Color. Colorless

Odor Sweetish, Hydrocarbon-like

Odor Threshold (ppm) Not available pH (Value) Not available

 $\begin{array}{ll} \text{Melting Point (°C) / Freezing Point (°C)} & \text{Not available} \\ \text{Boiling point/boiling range (°C):} & 34 - 35 \text{ (Diethylether)} \\ \text{Flash Point (°C)} & -45 \text{ (Diethylether)} \end{array}$

Evaporation Rate Not available Flammability (solid, gas) Extremely flammable

Explosive Limit Ranges 1.85% - 36.5% v/v (Diethylether)

Vapor pressure (Pascal) 7.16 x 10⁴ (Diethylether)

Vapor pressure (Pascal)

Vapor Density (Air=1)

Not available

Density (g/ml)

Solubility (Water)

Solubility (Other)

Partition Coefficient (n-Octanol/water)

Not available

Not available

Not available

Auto Ignition Point (°C) 175 (Diethylether)
Decomposition Temperature (°C) Not available
Kinematic Viscosity (cSt) Not available
Explosive properties Not available
Oxidizing properties Not available

Other information Not available

SECTION 10: STABILITY AND REACTIVITY

Reactivity Stable under normal conditions.

Chemical stability Stable.

Possibility of hazardous reactions None anticipated.

Conditions to avoid Avoid contact with heat and ignition sources.

Incompatible materials This product should be stored away from sources of strong heat or

oxidizing chemicals.

Hazardous decomposition product(s)

Carbon monoxide, Carbon dioxide, Acrid smoke

SECTION 11: TOXICOLOGICAL INFORMATION

Exposure routes: Inhalation, Skin Contact, Eye Contact

Information on toxicological effects

Diethyl Ether (CAS# 60-29-7):

Acute toxicity Oral: LD50 = 1600 mg/kg-bw (rat)

Dermal: LD50 >20000 mg/kg-bw (rabbit) May cause drowsiness or dizziness.

 Irritation/Corrosivity
 Non-irritant to skin and eye.

 Sensitisation
 It is not a skin sensitiser.

 Repeated dose toxicity
 Not to be expected.

 Carcinogenicity
 Not to be expected.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

MutagenicityNot to be expected.Toxicity for reproductionNot to be expected.

Toluene (CAS#108-88-3):

Acute toxicity Oral LD50 = 5580 mg/kg (rat)

Dermal LD50 >5000 mg/kg (rabbit)

Inhalation LC50 (4 hour(s)) 28.1 mg/l (rat) - Vapours may cause

drowsiness and dizziness.

Irritation / Corrosivity Causes serious eye irritation. Causes skin irritation.

Sensitisation It is not a skin sensitiser.

Repeated dose toxicity Inhalation NOAEC = 1131 mg/m³ (rat), 2 Year(s) - May cause damage

to organs through prolonged or repeated exposure: neuropsychological

effects, auditory dysfunction and effects on colour vision.

Carcinogenicity It is unlikely to present a carcinogenic hazard to man.

NTP	IARC	ACGIH	OSHA	NIOSH
No.	No.	No.	No.	No.

Mutagenicity There is no evidence of mutagenic potential.

Reproductive toxicity Suspected of damaging the unborn child. NOAEC: 2.8 mg/liter (rat)

Chloroethane (CAS# 75-00-3)

Carcinogenicity

NTP	IARC	ACGIH	OSHA	NIOSH
Clear Evidence in Female Mice	No.	A3 - Confirmed Animal Carcinogen	No.	Yes.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

Short term Not available.
Long Term Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal should be in accordance with local, state or national legislation. Consult an accredited waste disposal contractor or the local authority for advice.

SECTION 14: TRANSPORT INFORMATION

	U.S. DOT	Sea transport (<u>IMDG)</u>	Air transport (ICAO/IATA)
UN number	1954	1954	1954
Proper Shipping Name	Compressed gas, flammable, n.o.s. (contains diethyl ether and carbon dioxide)	Compressed gas, flammable, n.o.s. (contains diethyl ether and carbon dioxide)	Compressed gas, flammable, n.o.s. (contains diethyl ether and carbon dioxide)
Transport hazard class(es)	2.1	2.1	2.1
Packing group Environmental hazards Special precautions for user	Not applicable None assigned None assigned	Not applicable None assigned None assigned	Not applicable None assigned None assigned

Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code: Not applicable

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture:

TSCA (Toxic Substance Control Act) - Inventory Status: All components listed or polymer exempt.

Designated Hazardous Substances and Reportable Quantities (40 CFR 302.4):

Chemical Name	CAS No.	Typical %wt.	RQ (Pounds)
Diethylether	60-29-7	~58	100
Chloroethane	75-00-3	< 2	1000
Toluene	108-88-3	<1	1000

SARA 311/312 - Hazard Categories:

SARA 313 - Toxic Chemicals (40 CFR 372):

Chemical Name	CAS No.	Typical %wt.
Chloroethane	75-00-3	< 2
Toluene	108-88-3	<1

SARA 302 - Extremely Hazardous Substances (40 CFR 355):

Chemical Name	CAS No.	Typical %wt.	TPQ (pounds)
None			

California Proposition 65 List:

Chemical Name	CAS No.	Type of Toxicity
Toluene	108-88-3	Developmental, Female Reproductive
Chloroethane	45-00-3	Cancer

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements: 1-16.

Date of preparation: August 17, 2015

Hazard Statement(s) and Risk Phrases Listed in: SECTION 2:/ SECTION 3:

Hazard Statement(s)

- H220: Extremely flammable gas.
- H224: Extremely flammable liquid and vapour.
- H225: Highly flammable liquid and vapour.
- H280: Contains gas under pressure; may explode if heated.
- H302: Harmful if swallowed.
- H304: May be fatal if swallowed and enters airways.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H336: May cause drowsiness or dizziness.
- H351: Suspected of causing cancer.
- H361d Suspected of damaging the unborn child.
- H373: May cause damage to organs through prolonged or repeated exposure.
- H401: Toxic to aquatic life.
- H411: Toxic to aquatic life with long lasting effects.
- H412: Harmful to aquatic life with long lasting effects.

Training advice: None.

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.