

## EVOCHARGE® Level 2 Charging Stations on 6 ft. Pedestal (EVSE, iEVSE, iEVSE Plus) Product Description and Specifications

### ELECTRIC VEHICLE CHARGING STATIONS

- **Modern Compact Design:** EVSE form factor smaller than a standard sheet of letter-size paper
- **Robust Construction, Certified for Outdoor Use:** tamper-resistant features; NEMA 4 certified for outdoor and indoor use
- **Simple Operation:** EVSE models simply plug-in to EV and charge
- **Network Options:** iEVSE and iEVSE Plus are OCPP 1.6 networked enabled charging stations to support access control, payment capability, remote management and control, demand response. Network connection via Wi-Fi; iEVSE Plus models also include 4G-LTE cellular, RFID card reader and Local Load Management capability
- **Cable Management:** Standard Connector, Cable Holster, EVOREEL and 6 ft. pedestal included
- **Flexible Mounting Options:** pedestal/ground installation, Single & Dual port and cable length options available



<b>Part Number</b>	EVOCHARGE EVSE: Single EVC4AA0C1B1A3 or Dual EVC4AA0C1B1B3 (22 ft. charge cable) EVOCHARGE iEVSE: Single EVC4AB0C1B1A3 or Dual EVC4AB0C1B1B3 (22 ft. charge cable) EVOCHARGE iEVSE Plus: Single EVC4AC0C1B1A3 or Dual EVC4AC0C1B1B3 (22 ft. charge cable) Optional 30 ft. charging cable available.
<b>Connector / EVSE Level</b>	SAE J1772; AC Level 2
<b>Max Output Rating</b>	30A; 7.2 kW Maximum Output – For use with dedicated 40A (or greater) Supply Circuit
<b>Alternate Adjustable Output Settings</b>	24A; 5.76 kW Maximum Output – For use with 30A Circuit Rating 16A; 3.84 kW Maximum Output – For use with 20A Circuit Rating
<b>Electrical Circuit / Input Power Requirements</b>	208-240VAC, 50/60 Hz., Single Phase; Circuit Requirement: Dedicated; Branch Breaker: Double pole; Circuit Conductors: Line 1, Line 2, Earth Ground
<b>Input Power Connection</b>	Hardwire
<b>Operational Ratings</b>	NEMA 4, Indoor/Outdoor Rated; Temp: -22°F to 122°F (-30°C to 50°C); Humidity: 95% RH
<b>Mounting</b>	Pedestal Installation (single or dual port/charging station mount)
<b>Dimensions</b>	EVSE: 11.0 x 7.5 x 3.2 inches (28.0 x 19.0 x 8.1 cm), EVOREEL 13.8 X 12.0 X 9.2 inches (35.1 x 30.1 x 23.4 cm), Pedestal 6 ft. (1.8 m) tall
<b>Display &amp; Indicators</b>	LED Charge Status Indicators (Power/Ready, Charging, Fault)
<b>Cable Management Type</b>	Connector/Cable Holster (Standard) and EVOREEL
<b>Standards &amp; Compliance</b>	Charging Station: UL/cUL Listed; SAE J1772, UL 2594, UL 355, CSA; EVOREEL: ETL/cETL

\*visit [phillipsandtemro.com](http://phillipsandtemro.com) for more information or to download an installation manual