



Cold Weather Fuel Gelling Solutions

FEATURES

BENEFITS

- Minimizes down time
- Prevent costly truck-down repairs
- Reduce the need for fuel additives

APPLICATIONS

- OEM
- Aftermarket

IN-LINE FUEL HEATER

- Provides heat to the fuel filter
- Simple in-line installation before fuel filters
- Thermostatically controlled to prevent overheating
- Diesel & BioDiesel up to B100 Compatible
- Available electric pre-heat option
- Available as aftermarket retro-fit install



I-909BT-B100



I-909BTEH-B100

HOT FOX™ IN-TANK FUEL HEATER WITH SHUT OFF THERMOSTAT

- Exchanges heat from engine coolant to warm fuel as it's drawn up from fuel tank
- Thermostatically controlled to prevent overheating
- Installs in standard fuel tank sending port as OEM specified option or aftermarket retro-fit
- Models available with integrated auxiliary fuel standpipe for APU/ Diesel fired coolant heater applications
- Certain applications require the use of a reinforcement kit. See catalog for additional information.



Electric Fuel Heating Solutions

HOTLINE® ELECTRIC HEATER

- Thermal element runs inside fuel line providing heat to fuel
- Installs between fuel tank and fuel filter
- Used as a pre-heater only, prior to engine starting
- Available 2' – 12' lengths, 12 or 24V, 150 – 600w options
- OEM specified option or aftermarket retro-fit installation



FUEL FILTER WRAP

- Provides heat to the filter core, prior to start of engine to prevent filter clogging
- Electric silicone pad wraps around spin-on fuel filter with velcro adjustment
- Used as a pre-heater, run 15-30 minutes prior to engine start
- Fits diesel fuel filters from 2-3/4" – 5" (8.9 – 12.7cm)



Part No.	Watts	Volts	Amp	Height	Fits Filter Diameter	Plug Type	Cord Length	T-Stat	Certifications
3400039	50	12 DC	4.2	3.0" (7.6 cm)	2-1/2 to 3-1/2" (6.4 to 8.9cm)	Blunt - 2 Wire	6' - 72" - 1.8m	-	-
3400037	100	12 DC	8.3	4" (10.2 cm)	3-3/4 to 5" (9.5 to 12.7cm)	Blunt - 2 Wire	6' - 72" - 1.8m	-	-
3400040	100	24	4.2	4" (10.2 cm)	3-3/4 to 5" (9.5 to 12.7cm)	Blunt - 2 Wire	6' - 72" - 1.8m	-	-
3400101	40	120	0.3	2-1/4" (5.7 cm)	2-1/2 to 3-3/8" (6.4 to 8.6cm)	E - Nema 1-15P	6' - 72" - 1.8m	-	-
3400124	100	120	0.8	4" (10 cm)	3-3/4 to 5" (9.5 to 12.7cm)	E - Nema 1-15P	6' - 72" - 1.8m	-	-