



Zerostart[®]

**SILICONE
PAD HEATERS**

PHILLIPS & TEMRO
industries[®]

SILICONE PAD HEATERS

ADHESIVE – SILICONE PAD HEATERS



Silicone pad heater that is easily installed with adhesive mounting and silicone weatherproofing for installation on smooth metal surfaces. Warm internal engine components for quick starts and reduce engine wear by improving the flow of engine fluids. Cord Length: 6' (1.8 m)

Part No.	Volts	Watts	Amp	Width	Length	Plug Type	Thermostat	Certifications				Oil Pan Capacity		Hydraulic/Transmission Fluid Capacity	
								US & Can	US	US & Can	Europe	Qts/Gal	Liters	Qts/Gal	Liters
3400030	120	50	0.4	1-1/4" (3cm)	3-1/2" (9cm)	A - Nema 5-15	170-200°F (77-93°C)	Yes				1 - 3 Qts	0.94 - 2.8	Less than 1 Gal	
3400032	120	125	1	1-1/2" (4cm)	6" (15cm)	A - Nema 5-15	170-200°F (77-93°C)	Yes				3 - 6 Qts	2.8 - 5.7	1-7 Gal	3.8 - 26.5
3400119	120	125	1	1-1/2" (4cm)	6" (15cm)	A - Nema 5-15	270-300°F (132-149°C)	Yes				3 - 6 Qts	2.8 - 5.7	Up to 5 Gal	Up to 18.9
3400031	120	125	1	3" (7.6cm) Round	3" (7.6cm) Round	A - Nema 5-15	170-200°F (77-93°C)	Yes				3 - 6 Qts	2.8 - 5.7	1 - 7 Gal	3.8 - 26.5
3400033	120	250	2.1	3-1/2" (9.5cm)	4-1/2" (11cm)	A - Nema 5-15	170-200°F (77-93°C)	Yes				5 - 13 Qts	4.7 - 12.3	10 - 30 Gal	37.9 - 113.6
3400121	120	250	2.1	3-1/2" (9.5cm)	4-1/2" (11cm)	A - Nema 5-15	270-300°F (132-149°C)	Yes				5 - 13 Qts	4.7 - 12.3	6 - 16 Gal	22.7 - 60.6
3400087	120	420	3.5	4-1/2" (11cm)	6-1/2" (16.5cm)	A - Nema 5-15	270-300°F (132-149°C)	Yes				13 - 27 Qts	12.3 - 25.5	20 - 50 Gal	75.7 - 189.3
3400034	120	500	4.2	5" (13cm)	7" (18cm)	A - Nema 5-15	170-200°F (77-93°C)	Yes				13 - 27 Qts	12.3 - 25.5	20 - 50 Gal	75.7 - 189.3
3400122	120	500	4.2	5" (13cm)	7" (18cm)	A - Nema 5-15	270-300°F (132-149°C)	Yes				13 - 27 Qts	12.3 - 25.5	16 - 32 Gal	60.6 - 121.1
3400035	120	1000	8.3	6" (15cm)	10-3/4" (27cm)	A - Nema 5-15	170-200°F (77-93°C)	Yes				26 - 48 Qts	24.6 - 45.4	50 - 100 Gal	189.3 - 378.5
3400123	120	1000	8.3	6" (15cm)	10-3/4" (27cm)	A - Nema 5-15	270-300°F (132-149°C)	Yes				26 - 48 Qts	24.6 - 45.4	31 - 100 Gal	117.3 - 378.5
3400082	240	125	0.5	1-1/2" (4cm)	6" (15cm)	B - Nema 6-15	270-300°F (132-149°C)	Yes			Yes	3 - 6 Qts	2.8 - 5.7	Up to 5 Gal	Up to 18.9
3400083	240	250	1	3-1/2" (9.5cm)	4-1/2" (11cm)	B - Nema 6-15	270-300°F (132-149°C)	Yes			Yes	5 - 13 Qts	4.7 - 12.3	6 - 16 Gal	22.7 - 60.6
3400084	240	500	2.1	5" (13cm)	7" (18cm)	B - Nema 6-15	270-300°F (132-149°C)	Yes			Yes	13 - 27 Qts	12.3 - 25.5	16 - 32 Gal	60.6 - 121.1
3400085	240	1000	4.2	6" (15cm)	10-3/4" (27cm)	B - Nema 6-15	270-300°F (132-149°C)	Yes			Yes	26 - 48 Qts	24.6 - 45.4	31 - 100 Gal	117.3 - 378.5
3400070	12 DC	7	0.6	1" (2.5cm)	2" (5.1cm)	Blunt - 2 Wire				Yes	Yes	Spot heating, valves & fittings			
3400071	12 DC	80	6.7	1-1/2" (4cm)	8" (20cm)	Blunt - 2 Wire				Yes	Yes			0.5 - 6 Qts	0.47 - 5.7
3400051	12 DC	50	4.2	3" (7.6cm) Square	3" (7.6cm) Square	Blunt - 2 Wire				Yes	Yes			1 - 5 Qts	0.94 - 4.7
3400052	12 DC	125	10.4	4" (10 cm)	4" (10 cm)	Blunt - 2 Wire				Yes	Yes			2 - 3 Gal	7.6 - 11.4
3400110	120	300	2.5	8-1/2" (21.6 cm)	14-1/2" (37cm)	A - Nema 5-15				Yes		5 - 13 Qts	4.7 - 12.3	10 - 30 Gal	37.9 - 113.6

SILICONE PAD HEATERS – DIESEL FUEL FILTER



Flexible silicone pad heater that snugly wraps around metal diesel fuel filters with a with a hook & loop closure.

- Use with metal filters only
- Fits diesel fuel filters from 2-3/4" – 5" (8.9 – 12.7cm)

Part No.	Watts	Volts	Amp	Height	Fits Filter Diameter	Plug Type	Cord Length	T-Stat	Certifications
3400039	50	12 DC	4.2	3.0" (7.6 cm)	2-1/2 to 3-1/2" (6.4 to 8.9cm)	Blunt - 2 Wire	6' - 72" - 1.8m	-	-
3400037	100	12 DC	8.3	4" (10.2 cm)	3-3/4 to 5" (9.5 to 12.7cm)	Blunt - 2 Wire	6' - 72" - 1.8m	-	-
3400040	100	24	4.2	4" (10.2 cm)	3-3/4 to 5" (9.5 to 12.7cm)	Blunt - 2 Wire	6' - 72" - 1.8m	-	-
3400101	40	120	0.3	2-1/4" (5.7 cm)	2-1/2 to 3-3/8" (6.4 to 8.6cm)	E - Nema 1-15P	6' - 72" - 1.8m	-	-
3400124	100	120	0.8	4" (10 cm)	3-3/4 to 5" (9.5 to 12.7cm)	E - Nema 1-15P	6' - 72" - 1.8m	-	-

120 volt models are not available for use in Canada

SILICONE PAD HEATERS - BATTERY

Silicone pad heater placed underneath the batteries.

- Silicone material is resistant to battery acid
- Slim design to fit in the battery box/tray
- Cord Length: 6' (1.8 m)



Part No.	Watts	Volts	Amp	Width	Length	Plug Type	T-Stat	Certifications			
								US & Can	US	US & Can	Europe
3400066	60	120	0.5	5-1/2" (14 cm)	8-1/2" (21.6 cm)	E - Nema 1-15P	-	-	Yes	-	Yes
3400036	60	120	0.5	5-1/2" (14 cm)	8-1/2" (21.6 cm)	A - Nema 5-15	-	Yes	-	-	Yes
3400104	80	120	0.7	6-1/2" (16.5cm)	10-1/2" (26.7 cm)	E - Nema 1-15P	-	-	Yes	-	Yes
3400038	180	120	1.5	20-1/2"	13" (33 cm)	A - Nema 5-15	-	Yes	-	-	Yes
3400068	180	120	1.5	20-1/2"	13" (33 cm)	E - Nema 1-15P	-	-	Yes	-	Yes
3400086	60	240	0.25	5-1/2" (14 cm)	8-1/2" (21.6 cm)	B - Nema 6-15	-	Yes	-	-	Yes

NOTICE: This product is **NOT** recommended for use with lithium ion batteries, nickel cadmium batteries or with battery case material ABS.

Non CSA models are not available for purchase in Canada.

UL recognized models are available and can be sold to OEM manufacturers.

9700 West 74th Street, Eden Prairie, MN 55344
Phone: 952-941-9700 Toll-Free: 1-800-328-6108
sales@phillipsandtemro.com

PHILLIPS & TEMRO
industries®

phillipsandtemro.com